

Twin cavity Precijet+ 6 + 10 level GN 1/1 electric ovens

Ref. BPPE0610/1-11

PRECIJET+ THE ESSENTIALS

Intelligent cooking®:

CoreControl: power is adjusted to suit the load
AirControl®: speed control and auto fan reverse
JetControl: advanced injection technology
Rapid cooling of the oven cavity

FastPAD:

Touch control panel, intuitive and ergonomic

Integral TwinControl:

Exclusive patented system doubling the essential oven functions

Full Cleaning System:

Cleaning system with automatic chemical supply

Consobox:

Tracks the ovens historic consumption levels



TECHNICAL SPECIFICS

- * FastPAD® toughened glass control panel: comprising two large colour LCD touch screens and coding knobs.
- * **Aircontrol®:** Auto reverse ventilation, adjustable from 1 to 100%.
- * **Airdry+ :** Rapid product drying by opening the motorised vent, for a crispier exterior, ventilation provided by 1 fan.
- * **CoreControl:** Automatic adjustment of the oven power to suit the load being cooked, for results that are always to the precise degree required.
- * Continuously available thanks to immediate adjustment to the required temperature.
- * Power down: Automatically switches to energy saving mode after a period of inactivity (adjustable).
- * The oven can be preheated out of hours.
- * Cooking cavities fitted with runners, one giving a capacity of **6 levels** GN 1/1 (325 x 530mm) spaced **83mm** apart and the other with a capacity of **10 levels** GN 1/1 (325 x 530mm) spaced **67mm** apart.
- * **«FullCleaning System»** Automatic cleaning programme: Automatic cleaning with integral chemical pump. 3 possible levels of cleaning.
- * **7 cooking modes:**
 - Convection from 0 to 250°C
 - Saturated steam: steam to 98°C
 - Combined from 30 to 250°C (with humidity adjustable from 0 to 99%)
 - Low temperature: steam from 30 to 97°C
 - High temperature steam: steam from 99 to 105 °C
 - Regeneration
 - Delta T.
- * **Automatic cooking mode:**
 - Immediate access to cooking programmes.
 - 80 preloaded recipes as standard with the option to adjust the degree of cooking and the colouration
 - It is possible to create entirely personalised recipes
 - Displayed as text or as pictures via the library within the oven
 - Recipes are classified by family and / or in « my recipes ».
- * **Service mode**
 - Tracking software kit supplied with the oven
 - Transfer recipes and photographs via a computer
 - Parameters can be modified to give maximum personalisation
 - Visual Diagnostic System: interactive screen intended for technicians.
- * **Functions**
 - **Automatic** oven cavity **cooling**, door closed: improved reactivity
 - **Humidifier** : provides instant steam (shot of vapour): ideal for bread
 - **Hold function** : temperature holding phase after cooking (semi static oven). Avoids the surface of the product drying out
 - **Automatic rinse** possible between cooking operations, replaces the spray hose
 - **MultiTimer:** cooking times can be programmed for each level : bringing greater flexibility during service.
- * **Equipment**
 - Cool touch athermic double glazed clipped door with left or right hand rotation of the handle to open, hinged to the left and a simple push closure. Opens to 180° with hinged internal glass to make cleaning easier
 - Cavity illumination by a strip of LEDs in the door
 - Condensation recovery channel under the door and below the oven drains continuously
 - Features electrical protection, a door safety and thermal overload protection.
- * **Standard supply**
 - 1 set of runners with 6 level max capacity spaced 83mm apart + 1 set with 10 levels 67mm apart
 - 2 removable core probes, Rotisserie model 4.5mm diameter 100mm long
 - USB port.

ACCESSORIES / OPTIONS

- * 8 level runners with 63mm gap for 6 levels GN1/1 ovens.
- * 20 levels rack kit with "optimum gap" for 10 levels GN1/1 ovens (multilevel stainless runners optimise the available space to suit the depth of containers or the product to be cooked).
- * Removable core probe for delicate products, probe 2.5mm diameter 100mm long.
- * HACCP record output kit: HACCP outlet comprises 2 x 10m copper cables exiting the rear.
- * Energy economiser kit.
- * Retracting spray hose kit.
- * Independant spray hose kit.
- * Hood (see specific technical data sheet).
- * Grills (3 or 5).
- * Handed oven door (hinge on right).
- * Three phase 230V + Earth option.
- * 60Hz option.

NORMS: Conforms to

EN 60-335-2-42: European norm relating to the safety of electrical appliances.

(French norm: classification index C 73-842).

IP 25 and IK 9: Protection indices.

XP U 60-010: Hygiene.

BPPE0610/1-11

ELECTRICAL connection
Electric inlet at 310mm from the floor.
Protection required:
- 400V: 50A MCB (Miniature Circuit Breaker) with B curve and 30mA RCD (Residual Current Device)


Potable COLD WATER
Water inlet at 140mm from the floor.
A local stop cock is required.

SOFTENED WATER
Water inlet at 140mm from the floor.
A local stop cock is required.

DRAIN
Drain outlet at 105mm from the floor.
The water discharged could be condensate and at very high temperature, use material that is suitable for high temperatures.
There must be a trap between the unit and the mains drainage to prevent odours.

Vent with choke

Exit for surplus steam



MODEL

BPPE0610/1-11

DIMENSIONS (mm)

External
Cavity

Height 1945; Width 920; Depth 887
Height 552 / 722; Width 630; Depth 535

CAPACITIES

Number of covers per day	180 + 240
Usable oven capacity (dm ³)	85 + 115
GN 1/1 ovenware (325 x 530)	6 + 10
Max. depth of containers (mm)	65 / 55
Space between levels (mm)	83 / 67
Maximum capacity (kg)	24 + 40

PACKAGING (mm)

Height	2110
Width x Depth	1000 x 960

WEIGHT (KG) (gross / net)

257 / 226

CLEARANCES

Left: 4cm / Right: 50cm

TEMPERATURE RANGE

0 to 250°C

CORE TEMPERATURE RANGE

0-99°C

TIMER

99 hours

ELECTRICITY (Three phase 230V+E or 400V+N+E)

Voltage
400V 3Na.c.

I. Max (A)
37.4

Power (kW)
24.6

POTABLE COLD Water / SOFTENED Water

Pressure (Min / Max)	150/600 kPa (1.5 bar / 6 bar)
Cold water max temperature	23°C
Softened water max temperature	23°C
Nature	168 µm filter integral with the oven
Hardness (Softened water)	TH 4 to 7 °e (60 to 100 ppm)
Water quality	Chloride Cl ⁻ : ≤ 150 mg/l / Free Chlorine Cl ₂ : ≤ 0.2 mg/l / 6.5 ≤ PH ≤ 9
Conductivity	≥ 50 µS / cm
Connection	20/27 threaded (G 3/4)
Instant maximum consumption	5 L/min

DRAIN

Condensate temperature	Approx. 98°C
Connection	Vertical exit 40/49 threaded stainless (G 1"1/2)

CONSTRUCTION

Cavity and Cladding	18-10 Stainless
---------------------	-----------------

EQUIPMENT TYPE

Against a wall - Not stackable